

ROUGH TERRAIN CRANE

TR-200M

JAPANESE SPECIFICATIONS

OUTLINE	SPEC. NO.
Jib which stores in boom	TR-200M-4-00107

Control No. JA-01

TR-200M

CRANE SPECIFICATIONS

CRANE CAPACITY

8.5m Boom	20,000kg	at 3.5m	(7part-line)
14.6m Boom	16,000kg	at 3.5m	(6part-line)
20.7m Boom	9,000kg	at 6.0m	(4part-line)
26.8m Boom	6,800kg	at 7.0m	(4part-line)
7.4m Jib	3,000kg	at 70 °	(1part-line)
Single top	3,000kg		(1part-line)

MAX.LIFTING HEIGHT

Boom	27.5m
Jib	34.6m

MAX.WORKING RADIUS

Boom	25.0m
Jib	30.0m

BOOM LENGTH

8.5m – 26.8m

BOOM EXTENSION

18.3m

BOOM EXTENSION SPEED

18.3m/78s

JIB LENGTH

7.4m

MAIN WINCH SINGLE LINE SPEED

High range:	121m/min	(4th layer)
Low range:	58m/min	(4th layer)

MAIN WINCH HOOK SPEED

High range:	17.3m/min	(7 part-line)
Low range:	8.3m/min	(7 part-line)

AUXILIARY WINCH SINGLE LINE SPEED

High range:	103m/min	(2nd layer)
Low range:	50m/min	(2nd layer)

AUXILIARY WINCH HOOK SPEED

High range:	103m/min	(1 part-line)
Low range:	50m/min	(1 part-line)

BOOM ELEVATION ANGLE

0 °– 82 °

BOOM ELEVATION SPEED

0 °– 82 °/34s

SWING ANGLE

360 °continue

SWING SPEED

3.4rpm

WIRE ROPE

Main Winch

16mm x 150m (Diameter x Length)
7x7+6xFi(29) Class B ordinary Z twist
Spin-resistant wire rope
Breaking strength 17.6t

Auxiliary Winch

16mm x 80m (Diameter x Length)
7x7+6xFi(29) Class B ordinary Z twist
Spin-resistant wire rope
Breaking strength 17.6t

BOOM

4-section hydraulically telescoping boom of box construction
(stage 2: sequential; stages 3,4: synchronized)

BOOM EXTENSION

2 double-acting hydraulic cylinders
1 wire rope type telescoping device

JIB

Single stage which stores in the boom
Dual offset (0 °– 30 °) type

SINGLE TOP

Single sheave. Mounted on main boom head for single line work.

HOIST

Driven by hydraulic motor and via planetary gear reducer.
With free-fall device.
Automatic brake (with foot brake for free-fall device)
2 single winches

BOOM ELEVATION

1 double-acting hydraulic cylinder

SWING

Hydraulic motor driven planetary gear reducer
Swing bearing
Swing free/lock changeover type
Hand brake

OUTRIGGERS

Fully hydraulic X-type (floats mounted integrally)
Slides and jacks each provided with independent operation device.

Fully extended width	5.8m
Middle extended width	4.7m
Minimum extended width	3.6m

MAX. VERTICAL LOAD CAPACITY OF OUTRIGGER

22.6t

HYDRAULIC PUMPS

Variable piston pump and gear pump

HYDRAULIC OIL TANK CAPACITY

375 liters

SAFETY DEVICES

Automatic moment limiter (AML)
With working range limiting function
Over-winding cutout device
Working area control device
Level gauge
Hook safety latch
Winch drum lock
Hydraulic safety valve
Telescopic counterbalance valve
Elevation counterbalance valve
Jack pilot check valve
Swing lock

EQUIPMENT

Crane cab heater (with defroster)
Hydraulic oil temperature indication lamp
Oil cooler
Winch drum rotation indicator
Operation pedals for elevating/telescoping
Radio

CARRIER SPECIFICATIONS

ENGINE

Model	MITSUBISHI 6D14
Type	4-cycle, 6-cylinder, direct-injection, water-cooled diesel engine (with turbo charger)
Piston displacement	6,557cc
Max. output	185PS at 2,800rpm
Max. torque	58.0kg·m at 1,600rpm

TORQUE CONVERTER

3-element, 1-stage unit (with automatic lock-up mechanism)

TRANSMISSION

Power shift type (wet multi-plate clutch)
3 forward and 1 reverse speeds

REDUCER

Axle dual-ratio reduction

DRIVE

2-wheel drive (4X2) / 4-wheel drive (4X4) selection

FRONT AXLE

Full floating type

REAR AXLE

Full floating type (with no-spin differential)

SUSPENSION

Front Parallel leaf spring type
Rear Parallel leaf spring type

STEERING

Fully hydraulic power steering
With reverse steering correction mechanism

BRAKE SYSTEM

Service Brake
Hydro-pneumatic brake
Disk brake
Parking Brake
Mechanically operated, internal expanding duo-servo shoe type acting on drum at transmission case rear.
Auxiliary Brake
Electro-pneumatic operated exhaust brake
Auxiliary braking device for operations

FRAME

Welded box-shaped structure

ELECTRIC SYSTEM

12 V DC. 2 batteries of 24V (120Ah)

FUEL TANK CAPACITY

250 liters

TIRES

Front 14.00R24 (OR)
Rear 14.00R24 (OR)

CAB

Two-man type
With sun visor and trim
Rubber mounted type
Fully adjustable seat (with headrest and seat belt)
Adjustable handle (tilt, telescoping)
Roof windshield lock warning

SAFETY DEVICES

Emergency steering device
Spring lock device
Rear wheel steering lock device
Engine over-run alarm
Overshift prevention device
Parking brake alarm

GENERAL DATA

DIMENSIONS

Overall length	10,470mm
Overall width	2,490mm
Overall height	3,420mm
Wheel base	3,100mm
Tread Front	2,070mm
Rear	2,070mm

WEIGHTS

Gross vehicle weight	
Total	23,330kg
Front	11,665kg
Rear	11,665kg

PERFORMANCE

Max. traveling speed	49km/h
Gradeability (tan)	0.6
Min. turning radius	4.7m (4-wheel steering) 8.0m (2-wheel steering)

TOTAL RATED LOADS

(1) With outriggers set
(i)


Unit: ton

Outriggers fully extended								-360 °-	
B \ A	8.5m	14.6m	20.7m	26.8m		7.4m			
						0 °	30 °		
2.5m	20.0	16.0	9.0		82	3.0	2.0		
3.0m	20.0	16.0	9.0		75	3.0	2.0		
3.5m	20.0	16.0	9.0	6.8	70	3.0	2.0		
4.0m	18.5	15.5	9.0	6.8	65	2.6	1.85		
4.5m	16.5	14.3	9.0	6.8	60	2.2	1.7		
5.0m	15.0	13.2	9.0	6.8	55	1.8	1.55		
5.5m	13.7	12.2	9.0	6.8	50	1.4	1.25		
6.0m	12.5	11.4	9.0	6.8	45	1.05	1.0		
6.5m	11.5	10.6	8.5	6.8	40	0.85	0.8		
7.0m		9.9	8.1	6.8	35	0.7	0.65		
8.0m		8.0	7.3	6.15	30	0.55	0.55		
9.0m		6.5	6.5	5.55	25	0.45			
10.0m		5.45	5.65	5.05					
11.0m		4.55	4.8	4.65					
12.0m		3.8	4.15	4.25					
13.0m			3.6	3.8					
14.0m			3.15	3.25					
15.0m			2.75	2.8					
16.0m			2.4	2.5					
17.0m			2.1	2.25					
18.0m			1.85	2.0					
19.0m				1.75					
20.0m				1.55					
22.0m				1.2					
24.0m				0.9					
25.0m				0.8					

A= Boom length
B= Working radius
C= Jib length
D= Jib offset
E= Boom angle

(ii)


Unit: ton

Outriggers middle extended								-360 °-	
B \ A	8.5m	14.6m	20.7m	26.8m	 C D E (°)	7.4m			
						0 °	30 °		
2.5m	20.0	16.0	9.0		82	3.0	2.0		
3.0m	20.0	16.0	9.0		75	3.0	2.0		
3.5m	20.0	16.0	9.0	6.8	70	3.0	2.0		
4.0m	18.5	15.5	9.0	6.8	65	2.3	1.85		
4.5m	16.5	14.3	9.0	6.8	60	1.65	1.4		
5.0m	15.0	13.2	9.0	6.8	55	1.2	1.05		
5.5m	12.5	11.85	9.0	6.8	50	0.9	0.8		
6.0m	10.6	10.1	9.0	6.8	45	0.65	0.6		
6.5m	9.0	8.7	8.5	6.8	40	0.45	0.4		
7.0m		7.6	8.0	6.8					
8.0m		5.85	6.4	6.15					
9.0m		4.7	5.2	5.35					
10.0m		3.85	4.3	4.4					
11.0m		3.15	3.55	3.75					
12.0m		2.6	3.0	3.15					
13.0m			2.5	2.7					
14.0m			2.1	2.3					
15.0m			1.8	2.0					
16.0m			1.5	1.7					
17.0m			1.3	1.45					
18.0m			1.1	1.2					
19.0m				1.05					
20.0m				0.9					
22.0m				0.6					
24.0m				0.4					

A= Boom length
 B= Working radius
 C= Jib length
 D= Jib offset
 E= Boom angle

(iii)

Unit : ton

Outriggers minimum extended								-360 °-	
B \ A	8.5m	14.6m	20.7m	26.8m	 C D E (°)	7.4m			
						0 °	30 °		
2.5m	20.0	16.0	9.0		82	3.0	2.0		
3.0m	20.0	16.0	9.0		75	3.0	2.0		
3.5m	18.8	16.0	9.0	6.8	73	3.0	2.0		
4.0m	14.5	13.6	9.0	6.8	72	2.8	2.0		
4.5m	11.5	11.1	9.0	6.8	70	2.3	1.75		
5.0m	9.5	9.1	9.0	6.8	65	1.45	1.2		
5.5m	8.0	7.65	8.1	6.8	60	0.95	0.8		
6.0m	6.9	6.55	6.95	6.8	55	0.55	0.5		
6.5m	6.0	5.7	6.1	6.3					
7.0m		5.0	5.3	5.55					
8.0m		3.8	4.2	4.35					
9.0m		2.95	3.35	3.55					
10.0m		2.35	2.75	2.9					
11.0m		1.85	2.25	2.4					
12.0m		1.45	1.8	2.0					
13.0m			1.5	1.65					
14.0m			1.25	1.35					
15.0m			1.0	1.1					
16.0m			0.8	0.9					
17.0m			0.6	0.75					
18.0m			0.4	0.6					
19.0m				0.45					

A= Boom length
 B= Working radius
 C= Jib length
 D= Jib offset
 E= Boom angle

PRECAUTIONS TO BE TAKEN WHEN THE OUTRIGGERS ARE EXTENDED:

1. The total rated loads shown are for the case where the outriggers are set horizontally on firm level ground.
The values above the bold lines are based on the crane strength while those below are based on the crane stability.
2. The weights of the slings and hooks (main hook: 220kg, auxiliary hook: 60kg) are included in the total rated loads shown.
3. The total rated load is based on the actual working radii including the deflection of the boom.
4. The chart below shows the standard number of part lines for each boom length. The load per line should not exceed 2.9t for the main winch and 3.0t for the auxiliary winch.

A	8.5m	14.6m	20.7m	26.8m	J
H	7	6	4	4	1

A= Boom length H= No. of part-lines

J= Jib/Single top

5. As a rule, free-fall operation should be performed only when lowering the hook alone. If a hoisted load must be lowered by free-fall operation, the load must be kept below 1/5th of the total rated load and sudden braking operations must be avoided.
6. The total rated load for the single top shall be the value obtained by subtracting 160kg from the total rated load of the boom and must not exceed 3.0t.

(2) Without outriggers

Unit: ton

B (m)	Stationary						Creep (travelling at 1.6km/h or less)					
	8.5m Boom		14.6m Boom		20.7m Boom		8.5m Boom		14.6m Boom		20.7m Boom	
	F	G	F	G	F	G	F	G	F	G	F	G
3.0	12.2	8.2	8.7	7.2			8.5	6.5	6.7	5.0		
3.5	10.7	7.2	8.7	7.0	6.2	4.5	8.3	5.6	6.7	5.0	5.2	3.7
4.0	10.2	6.0	8.7	5.6	6.2	4.5	7.5	4.7	6.7	4.6	5.2	3.7
4.5	9.1	4.9	8.0	4.5	6.2	4.5	6.8	3.7	6.3	3.7	5.2	3.7
5.0	8.0	4.0	7.2	3.75	6.2	4.1	6.1	3.1	5.8	3.0	5.2	3.3
5.5	6.9	3.4	6.4	3.2	5.7	3.5	5.4	2.6	5.2	2.5	4.8	2.8
6.0	6.1	2.8	5.65	2.7	5.3	3.0	4.9	2.2	4.6	2.1	4.4	2.3
6.5	5.2	2.4	4.9	2.2	4.85	2.55	4.2	1.8	4.05	1.7	4.0	2.0
7.0			4.3	1.85	4.5	2.2			3.6	1.4	3.7	1.7
8.0			3.3	1.25	3.7	1.65			2.75	0.9	3.1	1.2
9.0			2.55	0.8	3.0	1.2			2.15	0.6	2.5	0.9
10.0			2.05	0.4	2.5	0.85			1.75		2.05	0.6
11.0			1.6		2.0	0.55			1.35		1.65	
12.0			1.25		1.6				1.05		1.3	
13.0					1.3						1.05	
14.0					1.05						0.85	
15.0					0.85						0.65	
16.0					0.65						0.5	
17.0					0.45							

B= Working radius F= Front G= 360 °

PRECAUTIONS TO BE TAKEN WHEN THE OUTRIGGERS ARE NOT MOUNTED:


1. The total rated loads shown are for the case where the crane is set on firm level ground. The values above the bold lines are based on the crane strength while those below are based on the crane stability. The foundation, working conditions, etc. should be taken into consideration adequately when using the crane for actual work. (Tire air pressure: 9.00kg/cm²)
2. The weights of the slings and hooks are included in the total rated loads shown.
3. The total rated loads are based on the actual working radii into which are included the deflection of the boom and the tires.
4. The chart below shows the standard number of part lines for each boom length. The load per line should not exceed 2.9t (for the main winch).

A	8.5m	14.6m	20.7m	Single top
H	7	6	4	1

A= Boom length H= No. of part-lines


5. The total rated load for the single top shall be the value obtained by subtracting 120kg from the total rated load of the boom and must not exceed 3.0t.
6. Free-fall operations should not be performed without outriggers.
7. The 26.8m boom and the jib should not be used without the outriggers.
8. The boom must be kept inside a 2° area (1° each to the left and right) over front of the carrier when performing "Over front" crane operations without the outriggers.

Approx.2 °



9. When creeping while hoisting a load, the swing brake should be applied, the load should be kept as close to the ground as possible but not touching the ground and the speed should be kept at 1.6km/h or less. In particular, any abrupt steering, starting or braking must be avoided.
10. Crane operations should not be performed when creeping while hoisting a load.


WORKING RADIUS - LIFTING HEIGHT



NOTES:

1. The deflection of the boom is not incorporated in the figure above.
2. The figure above is for the case where the outriggers are fully extended (360°).

DIMENSIONS (1/100)



MEMO

A series of horizontal dashed lines for writing, consisting of 20 lines.